


Girella con dado in ottone o acciaio inox e guarnizione piatta in EPDM

Adaptor with union nut in brass/stainless steel and EPDM flat seal

Anschlussverschraubung mit EPDM-Flachdichtung und Messing-oder Inoxmutter

Code	d - G (ISO 228)	Dado Nut Überwurfm.	L	Z		MOQ
S60PC-LBP	15-G$\frac{1}{2}$		52	22	65	50
S60QC-LBP	15-G$\frac{3}{4}$		50	22	90	50
S60SC-LBP	15-G$1\frac{1}{4}$		51	20	190	15
S60QD-LBP	18-G$\frac{3}{4}$	Ottone	36	8	66	50
S60RE-LBP	22-G1	Brass	39	7	106	50
S60RF-LBP	28-G1	Messing	60	26	159	50
S60SF-LBP	28-G$1\frac{1}{4}$		44	10	168	50
S60TF-LBP	28-G$1\frac{1}{2}$		73	38	170	50
S60TG-LBP	35-G$1\frac{1}{2}$		48	11	260	20
S60UH-LBP	42-G$1\frac{3}{4}$		53	9	292	20
S60VH-LBP	42-G2		57	11	509	20
S60WJ-LBP	54-G$2\frac{3}{8}$		61	10	454	20